US 20190084364A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2019/0084364 A1**

LAGRANDCOURT et al. (43) **Pub. Date: Mar. 21, 2019**

(54) **VERSATILE URBAN ELECTRIC TRANSPORT DEVICE AND SYSTEM**

(71) Applicant: **Ford Global Technologies, LLC**, Dearborn, MI (US)

(72) Inventors: **Aurelien LAGRANDCOURT**, Preston (AU); **Navneet BHASIN**, Preston (AU)

(21) Appl. No.: **16/087,638**

(22) PCT Filed: **Sep. 9, 2016**

(86) PCT No.: **PCT/US16/50884**

§ 371 (c)(1),
(2) Date: **Sep. 22, 2018**

Related U.S. Application Data

(60) Provisional application No. 62/311,981, filed on Mar. 23, 2016.

Publication Classification

(51) **Int. Cl.**

B60G 17/0165	(2006.01)
B62D 51/02	(2006.01)
B60B 19/00	(2006.01)
B60K 7/00	(2006.01)
B60K 1/04	(2006.01)

(52) **U.S. Cl.**

CPC ***B60G 17/0165*** (2013.01); ***B62D 51/02*** (2013.01); ***B60B 19/003*** (2013.01); ***B60K 7/0007*** (2013.01); *B60Y 2200/91* (2013.01); ***B60K 1/04*** (2013.01); *B60G 2800/019* (2013.01); *B60K 2001/0438* (2013.01); ***B60L 11/18*** (2013.01)

(57) **ABSTRACT**

Disclosed herein is a transport device with a platform that pivots relative to a frame of the transport device. A pivot angle of the platform is altered with an actuator controlled by a transport computer. The pivot angle is based, at least in part, on a predicted change in velocity, a determined change in ground surface, a determined ground slope, and a center of gravity of a user and of the transport device.